

# **DESOI PullDevice P-1**

#### No. 11525

## Description

mobile, pneumatic pulling device DESOI PullDevice P-1 with four double-acting cylinders and switching to automatic mode for pulling the ram injection lances.

## **Delivery range**

moving device, 4 x double-acting cylinders, 5/2-way oscillating valve, 3/2-way hand valve with locking function, reducing valve, incl. instruction manual

#### **Advantages**

- $\bullet$  Usable for ram injection lances G  $1\!\!4''$  or G  $1\!\!2''$
- Mobility by moving device
- Tightening speed adjustable
- Easy operation



- 1. Operating and control element
- 2. Feeder plate for pulling head

## Technical data

Scraper plate 1/2"

Supporting plate 490 x 490 x 50 mm

recillical uata	
Working pressure	3 – 8 bar
Starting power	ca. 800 - 2100 kg
Tightening (piston stroke)	max. 160 mm
Air consumption	approx. 700 - max. 900 l/min
Weight	43 kg
LxWxH	56 x 58 x 72 - 106 cm
Accessories	No.
Pulling head ¼" pneumatic	11530
Pulling head ½" pneumatic	11535
Scraper plate 1/4"	11516

All information and data in this technical data sheet are based on the current state of technology. We reserve the right to make technical modifications. The consumption data given here are average values based on experience therefore deviations cannot be excluded.

08/2018

11517

11518