

DESOI PowerInject EC-2

No. 10556

Description

The compact eccentric pump DESOI PowerInject EC-2 has been made for the application of aqueous solutions. The low-wearing valves ensure long life. With the suction basket fixed to the suction hose the material can be sucked directly out of the material container.

Material to be used

Aqueous solutions, e. g.:

- Micro emulsion
- Silicification products
- Siloxane

Delivery range

suction system, pressure control valve, manometer
0 – 40 bar, incl. instruction manual,
No. 16799: HP material hose - steel (Ø 6 mm, 5 m long, union nuts G ¼", solvent resistant),
No. 500-07-722: LP injection gun (0 – 60 bar, external thread G ¼", whip 0.3 m, mouth piece)

Advantages

- High flow rate
- Cannot run dry
- Compact design
- Easy operation and cleaning



1. Pressure gauge unit with manometer

2. Exact adjustment of pressure

Technical data

Supply	230 V
Motor power	0.37 kW
Working pressure - infinitely variable	1 – 20 bar
Delivery - infinitely variable	max. 2.4 l/min
Weight	22 kg
L x W x H	42 x 25 x 45 cm

Accessories

	No.
Spare and wear part set DESOI PowerInject EC-2	10558-EVS
Set of tools DESOI PowerInject EC-2	10558-WS