

DESOI AirPower L36-2C VA



No. 17532

Description

The reciprocating pump DESOI AirPower L36-2C VA achieves a delivery of max. 20 l/min at a mixing ratio of 1 : 1. Due to the big valves and pistons also highly viscous material can be used without any problems.

Material to be used

- 2 component injection resin

Delivery range

moving device, 3 m suction system Ø 20 mm with suction basket Ø 40 mm: component A: transparent, component B: black, 2 x manometer 0 – 400 bar, material hose connection: component A: external thread G ½", component B: external thread G ¾", return hoses Ø 13 mm: transparent, air connection set: claw coupling 42 mm, air plug NW 7.2, incl. instruction manual

Advantages

- Manometers at machine outlet for pressure control of each components
- Big material passage - suitable also for highly viscous material
- Adjustment of the material volume



1. Pressure regulator with manometer and anti-freeze device

2. Manometer combination

Technical data

Working pressure - infinitely variable	5 - 200 bar
Delivery rate	max. 20 l/min
Air consumption	2.5 m ³ /min
Transmission ratio	1 : 25
Mixing ratio	1 : 1
Air pressure	max. 8 bar
Weight	92 kg
L x W x H	110 x 55 x 65 cm

Accessories

	No.
Spare and wear part set DESOI AirPower L36-2C VA	17532-EVS
Set of tools DESOI AirPower L36-2C VA	17607-WS