

## DESOI AirPower L36-2C

No. 17533

### Description

The reciprocating pump DESOI AirPower L36-2C achieves a delivery of max. 20 l/min at a mixing ratio of 1 : 1. Due to the big valves and pistons also highly viscous material can be used without any problems.

### Material to be used

- 2 component injection resin

### Delivery range

moving device, 3 m suction system Ø 20 mm with suction basket Ø 40 mm: component A: transparent, component B: black, 2 x manometer 0 - 400 bar, material hose connection: component A: external thread G ½", component B: external thread G ¾", return hoses Ø 13 mm: transparent, air connection set: claw coupling 42 mm, air plug NW 7.2, incl. instruction manual

### Advantages

- Manometers at machine outlet for pressure control of each components
- Big material passage - suitable also for highly viscous material
- Adjustment of the material volume



1. Pressure regulator with manometer and anti-freeze device

2. Manometer combination

### Technical data

Working pressure - infinitely variable	5 - 200 bar
Delivery rate	max. 20 l/min
Air consumption	2.5 m <sup>3</sup> /min
Transmission ratio	1 : 25
Mixing ratio	1 : 1
Air pressure	max. 8 bar
Weight	92 kg
L x W x H	110 x 55 x 65 cm

### Accessories

	No.
Spare and wear part set DESOI AirPower L36-2C	17533-EVS
Set of tools DESOI AirPower L36-2C/VA	17533-WS