

DESOI AirPower L36-3C VA

No. 17610

Description

The reciprocating pump DESOI AirPower L36-3C VA achieves a delivery of max. 20 l/min at a mixing ratio of 1 : 1. Due to the big valves and pistons also highly viscous material can be used without any problems. All material conducting parts are made of stainless steel. The pump is equipped with a separate rinsing pump. The result is a very maintenance-friendly machine including suitable accessories.

Material to be used

- 2 component injection resin

Delivery range

moving device with wheel set, suction system, 2 x manometer 0 – 400 bar, rinsing pump type S25, incl. instruction manual

Advantages

- Manometers at machine outlet for pressure control of each components
- Big material passage - suitable also for highly viscous material
- Adjustment of the material volume



1. Pressure regulator with manometer and anti-freeze device

2. Manometer combination with suction hose

Technical data

Working pressure – infinitely variable	5 – 200 bar
Delivery rate	max. 20 l/min
Air consumption	2.5 m ³ /min
Transmission ratio	1 : 25
Mixing ratio	1 : 1
Air pressure	max. 8 bar
Weight	100 kg
L x W x H	127 x 57 x 64 cm

Rising pump type S25

Working pressure – infinitely variable	7 – 220 bar
Delivery	5 l/min
Transmission ratio	1 : 28

Accessories

Accessories	No.
Spare and wear part set DESOI AirPower L36-3C VA	17610-EVS
Set of tools DESOI AirPower L36-3C VA	17610-WS